



# 9900/F9900 Series Grade 1 Concealed V/R (CVR) Exit Device

**ANSI GRADE 1**  
**ANSI/BHMA A156.3-2014**  
**Type 7 & 8**  
Exceeds 500,000 Cycles



UL Listed for "A" Label Doors  
Rated Up to 3 Hours  
UL10C Positive Pressure Rated  
Conforms to UBC 7-2 (1997)  
UL305 Listed for Panic Hardware  
UL10B Neutral Pressure Rated



Comply with  
ANSI117.1 for  
Accessible and  
Usable Buildings  
and Facilities  
Standards

## SPECIFICATIONS

### CERTIFICATIONS

- ANSI Grade 1 approved, exceeds 500,000 cycles.
- UL Listed for up to 3hrs on "A" label Fire Doors.
- Comply with ANSI117.1 for accessible and usable Buildings and Facilities Standards.

### DOOR FITTING

- 1-3/4"~ 2" thick standard.

### DOOR WIDTH

- 36", rail can be cut from the end to fit door size down to 30".
- 48", rail can be cut from the end to fit door size down to 40".

### MOUNTING HEIGHT

- 39-3/16" from CL of Mortise Latch case to finished floor.

### STRUCTURE

- Head Cover – Plated Zinc Alloy.
- Chassis – Steel or Stainless Steel.
- End Cap – Plated Zinc Alloy.
- Rail Assembly – Heavy Gauge Extruded Aluminum.

### LATCH BOLT

- Top Latch: 3/4" throw.
- Bottom Latch: 1/2" throw.

### STRIKE

- Stainless Steel, Stainless Steel  
Top: 9572C, Bottom: 9575.

### FASTENERS

- 9900 – Furnished with wood & machine Screws.
- F9900 – Furnished with wood & machine Screws and extra Sex nuts and bolts (SNB).

### FINISH

- US32D (630) with anodized US26D aluminum body.
- US10B (613) Oil Rubbed Bronze.
- Special order for US26 (625) Polish Chrome.

### HANDING

- Reversible non-handed.

### DOGGING

- Standard for 9900.  
Cylinder Dogging Kit 9CD36/9CD48 available.

### ALARM

- Alarm Kit 9AK36/9AK48 available.



The Bottom Rod of F9900 can be omitted to use as Less Bottom Rod (LBR) with a UL listed Auxiliary Fire Latch (9279)

## DIMENSIONS

Projection: 3-17/64" maximum, 2-17/32" dogged.  
Overall Size: 8-5/64" Height x Width 33-5/32" or 45-5/32".

