

Trim Hardware

BOLTS

Surface Bolt

3" SB-103
4" SB-104
6" SB-106
12" SB-112



6" Flush Bolt
(Round)
FBR-106



6" Flush Bolt
(Square)
FBS-106



7" Mortise in Flush Bolt
MFBR-07



7" Mortise in Flush Bolt
MFBR-17 (Flip Type)



18" Mortise-In Extension Flush Bolt with Extension Rod
MEFB-18 (Flip Type)



MANUAL FLUSH BOLT



EFB-01

For Metal Door

For use on hollow metal or fire rated doors.

Standard with 12" ext. rod, extra length available in size 18", 24", 36" & 48".

Meets ANSI A156.16 for L14251

* Bolt head rod is adjustable



EFB-02

For Wood Door

For use with wood composite/ fire rated doors.

Meets ANSI A156.16 for L14261



H.D. Surface Bolt

8" HSB-8
12" HSB-12



AUTOMATIC FLUSH BOLT SET



AFB-01

For Metal Door

Faceplate: 1" x 6-3/4"
• 3hrs fire rating

Fully automatic - Bolts retract when active door is opened; bolts extend when active door is closed.

Thermal lock automatically locks inactive door under high fire/heat conditions. 9278 dust proof strikes are recommended for use together.



* Bolt head rod is adjustable

AFB-02

For Wood Covered Composite Doors

Faceplate: 1" x 8-1/2"
• 1-1/2hrs fire rating



SELF LATCHING FLUSH BOLT SET



SFB-01

For Metal Door

Faceplate: 1" x 6-3/4"
• 3hrs fire rating

Top bolt can be manually released by pressing plunger - Inactive door will re-latch automatically when closed.

Thermal lock automatically locks inactive door under high fire/heat conditions. 9278 dust proof strikes are recommended for use together.



SFB-02

For Wood Covered Composite Doors

Faceplate: 1" x 8-1/2"
• 1-1/2hrs fire rating



* Bolt head rod is adjustable

This combination eliminates the bottom flush bolt and eliminates floor preparation:

Metal Door –

3hrs fire rating

Wood Door –

20mins fire rating



AFB-19

Automatic Flush Bolt with Fire Bolt for metal door

* Bolt head rod is adjustable



AFB-29

Automatic Flush Bolt with Fire Bolt for wood door



SFB-19

Self-Latching Flush Bolt with Fire Bolt for metal door



SFB-29

Self-Latching Flush Bolt with Fire Bolt for wood doors



DUST PROOF STRIKE 9278

Spring loaded plunger returns to floor or threshold level anytime flushbolt is retracted.



AUXILIARY FIRE LATCH 9279

Installed in bottom door edge of active door to replace the bottom flush bolt. Temperature-actuated bolt automatic extends at 230F.